

4MP Dual-Band Wi-Fi CAMERA



Face-Recognition
มีระบบจดจำใบหน้า



AI Detection

มีระบบตรวจจับความเคลื่อนไหว
แจ้งเตือนเมื่อมีคนเดินผ่าน



Pan:350° / Tilt:100°

สามารถสั่งหมุน กับ-เงย
ได้อย่างอิสระ



Night Vision

สามารถมองเห็นได้แม้ในที่มืด
ด้วยระบบอินฟราเรด



Wide Angle of view

มุมมองภาพกว้าง 112 องศา



2.4GHz & 5GHz Wi-Fi

รองรับ Dual WiFi ทั้ง
2.4G และ 5 G



Two-way Audio

คุยโต้ตอบ ด้วยลำโพง
และ ไมค์คุณภาพสูง

QHD 4 MP
รับประกัน 2 ปีเต็ม

ITEMS	4MP Dual-Band Wi-Fi IP Camera	
Image Sensor	Sensor Type	1/2.6" CMOS
	Display Resolution	2K(2304x1536)
	Frame Rate	20fps (2K) /25fps (3MP) /25fps (1080P), downward adjustable
	Min. Illumination	0 Lux (With IR Illuminator)
Lens	Lens Type	f4mm,F2.2
	Angle of View	Horizontal:89° Diagonal : 112°
Video	Image Compression	H264
	Resolution	2K(2304x1536) 20fps,3MP(1204x1440)25fps,1080P(1920x1080) 25fps,720P(1280 x 720), VGA(640 x 480), QVGA(320 x 240)
	Stream	dual stream
	Image adjustment	The hue, brightness, contrast, saturation, sharpness are adjustable
Audio	Flip image	flip and mirror
	Infrared mode	Automatic or manual
	Pan/Tilt Angle	Horizontal:350° & Vertical: 100°
	Night visibility	13pcs IR-LEDs, night vision range up to 8 metres
	Input/Output	Supports Full Duplex Two-way Audio Built-in Mic & Speaker
	Audio Compression	PCM/G.726
	Wireless Standard	2.4G/5G dual-band, IEEE802.11b/g/n/ac
Network	Ethernet	One 10/100Mbps RJ45 port
	Data Rate	IEEE802.11b: 11Mbps(Max.); IEEE802.11g: 54Mbps(Max.); IEEE802.11n: 150Mbps(Max.); IEEE802.11ac: 433Mbps(Max.)
	Wireless Security	WPA, WPA2
	Wireless Setup	Supports EZLink&QR Code-Wave wireless setup
	Network Protocol	IP, TCP, UDP, HTTP, HTTPS, SMTP, FTP, DHCP, RTSP, ONVIF
	Remote Access	P2P
System Requirements	Operating System	Microsoft Windows XP,7,8,10;Mac OS,iOS, Android
	Browser	Microsoft IE9 and above version,Edge; Mozilla Firefox; Google Chrome; Apple Safari.
Other Features	Motion Detection	Alarm via E-Mail, upload alarm snapshot to FTP and mobile app
	Sound Detection	Alarm via E-Mail, upload alarm snapshot to FTP and mobile app
	WDR	Improve image clarity in complex scenario
	Zoom	6X digital zoom function
	User Accounts	Three levels user role
	Firewall	Supports IP Filtering
	Storage	128G Micro SD card, local and FTP storage,Foscam cloud storage
	Reset	Reset button is available
Power	Intelligent Assistant	Supports Alexa, Google assistant
	Power Supply	DC 5V/2A
Physical	Power Consumption	<6W
	Color	Black/White
	Dimension(mm)	74(L)*74(W)*119(H)
Environment	Net Weight	290g
	Operating Temperature	-10°C ~ 40° (14°F ~ 104°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temperature	-20°C ~ 60° (-4°F ~ 140°F)
Certification	Storage Humidity	0% ~ 90% non-condensing
		CE, FCC, RoHS,WEEE

ดาวน์โหลด Application
PIXELS HOME



Cloud Management
Access, manage and control
your cameras



Cloud Push
Get real-time text or image alert
notifications on your phone



Cloud Recording
Store alarm or continuous video
recordings in the cloud



Cloud Playback
See the whole event in your
video history

